



GV2500A

Portable Generators

Three performance classes for reliable power supply

The generators in the GV series are cost-effective synchronous generators offering a reliable power supply even throughout continuous operation. The GV series includes models in three different performance categories as well as AC and three-phase designs. In addition to application on construction sites, the portable generators can equally be used for industrial, commercial and agricultural applications.

Highlights

- Sturdy protective frame
- Large tank with long running time
- Compact dimensions
- Honda four-stroke motor
- No grounding necessary

Technical Data

■ Electrical - Output Details

Aggregate continuous power 1~ (COP)	2.1 KW
Aggregate maximum power (MAX)	2.1 KW

■ Mechanical Details

Length	623.0 mm
Width	409.0 mm
Height	500.0 mm
Operating weight	46.0 kg

■ Generator

Generator type	NSM K80 C
Output current 1~	10.0 A
Output voltage	230.0 V
Output frequency	50.0 Hz

Efficiency factor 1~	0.9 cos φ
Nominal speed	3,000.0 1/min
Phase	1.0 ~
Earthing system	Electrical separation

■ Environment Data

Degree of protection	IP23M
Sound power LWA, guaranteed	96.0 dB(A)

■ Electrical System

Main Circuit Breaker Rating	12.0 A
Available voltages 1~	230.0 V
Receptacle Type	2 x CEE7/3 (Typ F) 230V 16A 1~
Number of Sockets	2.0